



# *Black Vitreous*

*Enameled chimney pipe line for smoke extraction*

## APPLICATION

Smoke evacuation chimney for wood burning stoves and fires.

## REGULATION

EN 1856-2  
EN 1856-2  
EN 1856-2

## DESIGNATION

T600 NI D Vm L80080 G800  
T600 NI D Vm L80090 G800  
T600 NI D Vm L80110 G800

250mm STRAIGHT PIPE 500mm STRAIGHT PIPE 750mm STRAIGHT PIPE 1000mm STRAIGHT PIPE		ELBOW 45°	
ADJUSTABLE LENGTH 500-800 ADJUSTABLE LENGTH 350-550		90° TEE	
500mm STRAIGHT PIPE WITH ACCESS DOOR		DECREASER	
CONDENSATION COLLECTOR PIPE		FINISHING COLLAR	
ELBOW 88°		SHORT REGULAR STRAIGHT LENGHT WITH DAMPER	
ELBOW 72°		ADJUSTABLE WALL SUPPORT	
ELBOW 90°		ELBOW 45° SMOOTH	

GENERAL CHARACTERISTICS

Joint system between elements is male-female

MATERIALS

Wall  
Finishing

Cold rolled steel  
Matt black vitrified enamel

<p>GUYWIRE BRACKET</p>		<p>45° ELBOW WITH ACCESS DOOR</p>	
<p>M-M SLEEVE</p>		<p>90° ELBOW WITH ACCESS DOOR</p>	
<p>F-F SLEEVE</p>		<p>WEATHING COWL</p>	
<p>TEE PLUG</p>		<p>CHIMNEY CAP</p>	
<p>INCREASER</p>	<p>5"</p>  <p>4"</p>	<p>6"</p>  <p>5"</p>	<p>7"</p>  <p>6"</p>



0099 CE Mark

AENOR

Certified Entity



HETAS Approved Product



Institute GIORDANO



**Vda. de G.Marí Montañana S.A.**

Avda. de la Senyera, 30  
46133 Meliana (Valencia)

Tel.: +34 961 490 500

Fax: +34 961 494 134

Email: [practic@practic.es](mailto:practic@practic.es)

**[www.practic.es](http://www.practic.es)**