



*Pellet line*

## APPLICATION / USAGES

Smoke evacuation pipes for insertable pellet stoves.

## GENERAL CHARACTERISTICS

System of union between male-female elements. With sealing gasket P1.

250 MM STRAIGHT PIPE		M CHIMNEY CAP	
500 MM STRAIGHT PIPE		F CHIMNEY CAP	
1000 MM STRAIGHT PIPE		BAFFLE	
90° ELBOW		FINAL SECTION	
45° ELBOW		FINISHING COLLAR	
MFM 90° TEE+TEE PLUG		ADJUSTABLE WALL CLAMP	
MFF 90° TEE+TEE PLUG		TEE PURGE PLUG	

REGULATIONS

EN 1856-2 T200 P1 W V2 L80090 O100

MATERIALS

LOCALIZATION	DESCRIPTION
Wall	Cold rolled steel sheet
Finishings	Glazed enamel in matt black

DIAMETERS

Ø80 Ø100

F-F SLEEVE		MFM 90° SHORT PELLET TEE WITH PLUG	
M-M SLEEVE		MFF 90° SHORT PELLET TEE WITH PLUG	
80M TO 100F ADAPTOR		ANTIBURNS PELLET PIPE	
80F TO 100M ADAPTOR			



**Vda. de G.Marí Montañana S.A.**

Avda. de la Senyera, 30  
46133 Meliana (Valencia)

Tel.: +34 961 490 500

Fax: +34 961 494 134

Email: [practic@practic.es](mailto:practic@practic.es)

**[www.practic.es](http://www.practic.es)**